

DU3



Small in size, great in functionality

The **DU3** is a cost-effective IoT ready Data Unit which features a 2.8" color screen and membrane keypad for a user friendly interaction with the operator. This compact, pre-wired unit allows a quick and straightforward connection of any textile production machine type.

The embedded IoT broker allows direct access from any remote location or external IT application to all information available in the **DU3**.

Functions


- Manual entry of down time reasons
- Display production information: OEE, KPIs, efficiencies, meters produced ...
- Display planning information: actual job status, next jobs planned ...
- Energy monitoring

(all functions are subject to licensing)

Features

- Direct access to all pages
- Wireless (Bluetooth class 1 or Wi-Fi) connection to the central system
- Remotely operable from any device that has an HTML 5 browser with JavaScript
- Continued operation and machine monitoring in case of network or server failure (optional)
- On screen language selection and Asian languages supported
- Customizable screens using standard HTML and JavaScript

Machine connection configurations



One DU3 per machine

All **DU3** inputs/output are available for each machine. The **DU3** connects to the MES server:

- Wireless via Bluetooth with the **WDL-SERVER**
- Via Wi-Fi with a regular wireless access point

Technical specifications

Display and keyboard

- 2.8" color LCD (58 x 43 mm)
- QVGA: 320 x 240 pixels
- 4 keys

Housing

- Size: 110 x 87 x 36 mm (W x H x D)
- Weight: 160 g (without cable)

Power

- 24 Vdc, maximum 5 W
- Counter retention at power failure

Input/outputs for machine connections

- 8 multifunctional digital inputs
 - Stop reason input
 - Hardware counter maximum 20 kHz
 - One length counter (AB encoder)
 - 12/24 V level
- 1 open collector transistor output (needs an external relay)

Options

- Backup & recovery function allowing a minimum of 24 hours local data storage in case of server or network failure

Part numbers

- A9011811: **DU3** with 10 m cable
- A9011812: **DU3** with 20 m cable
- A901182: **DU3** configuration set (optional)
- B557261: Power supply 90-264 Vac / 120-370 Vdc input, 24 Vdc output, maximum 10 W

Communication with MES server

- Bluetooth (WDL)
 - Class 1
 - Maximum 32 Data Units per **WDL-SERVER**
- Wi-Fi (WLAN)
 - IEEE 802.11bgn
 - MQTT ready
 - Number of Data Units per access point depends on the quality of the access point

Ingress protection rating

- IP43 (objects > 1mm, spraying water)
- The **DU3** does not have a fan, nor ventilation holes.

Environment

- Operating temperature range: 0 to 50°C
- Relative humidity: 20 to 80% non-condensing

BMSvision Master systems

- **WEAVEMASTER**: for the textile industry
- **QUALIMASTER**: fabric inspection and optimized cutting
- **ENERGMASER**: energy monitoring system
- **SPINMASTER**: for spinning plants
- **FINIMASTER**: for textile finishing plants



BMSvision

In Pursuit of Productivity



www.bmsvision.com

© Belgian Monitoring Systems
Member of the **Savio** Group

BMS bv • Cotton Park, Spinnerijstraat 99/1, 8500 Kortrijk, Belgium
☎ +32 56 262 611 ☎ +32 56 262 690 ✉ sales@bmsvision.com

BMS Vision Ltd • Capricorn Park, Blakewater Road, Blackburn, Lancashire, BB1 5QR, United Kingdom
☎ +44 1254 662 244 ☎ +44 1254 267 100 ✉ sales@bmsvision.com

BMSvision LLC • 4420 Taggart Creek Road, Suite 112, Charlotte, North Carolina 28208, United States
☎ +1 704 392 9371 ☎ +1 704 399 5588 ✉ sales@bmsvision.com

BMSvision (Shanghai) Co., Ltd. • Room 402, Building A, No.800 Guangji Road, Hongkou District, Shanghai 200434, China
☎ +86 21 6044 4208 ✉ sales@bmsvision.com